

Buckeye International, Inc.

2700 Wagner Place Maryland Heights, MO 63043 314/291-1900

N. F. P. A.

4 = Extreme

3 = High

2 = Moderate

1 = Slight 0 = Insignificant

公	HEALTH	1
Ø.	FLAMMABILITY	0
X .	INSTABILITY	0

Material Safety Data Sheet

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956. 24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

	ON I - IDEN	TIFICATIO	N			
PRODUCT	NAME					DATE PREPARED
BUCKEYE EQUITY						June 2, 2008
CHEMICA	L FAMILY					CODE
		Buffing Floo	or Finish Enhancer	, Water/Solv	ent Mix	5108
PROPER D	O.O.T.					•
SHIPPING	NAME	Compound,	Polishing or Wax,	Liquid		
D.O.T. HAZ	ZARD	1 ,	<u> </u>	1		
CLASSIFIC	CATION	None				
			AND IDENTITY	INFORMA	TION	
% By WGT		MATERIAL		PEL	T.L.V.	C.A.S. NO.
8.0	Petroleum Hydr			NE	300 ppm	64742-47-8
>74.0	Soft Water			NE	NE	7732-18-5
<4.0	Polyethylene Gl	lycol		NE	NE	25322-68-3
<4.0	Polyurethane A	•	on	NE	NE	Blend
<4.0	Lauramide DEA	<u> </u>		NE	NE	120-40-1
<4.0	Polyethylene Er	nulsion		NE	NE	Blend
< 2.0	Perfume and Ac	ditives less that	n 1%	NA	NA	NA
ITEMS MA	ARKED * ARE SAR	A TITLE III SEC 31	3 REPORTABLES. ALL	INGREDIENTS A	RE ON TSCA INVI	ENTORY.
SECTIO	N III - PHY		ΓΑ	_	RE ON TSCA INVI	
SECTIC BOILING F	ON III - PHY POINT °F		Γ A 212°F	pH (CONC.)		9.2 ± 0.2
SECTIC BOILING F SOLUBILIT	ON III - PHY POINT °F TY IN WATER		TA 212°F Miscible	pH (CONC.) pH (USE DIL	UTION) RTU	9.2 ± 0.2 9.2 ± 0.2
SECTIC BOILING F SOLUBILIT W VOLATI	ON III - PHY POINT °F TY IN WATER ILE BY WEIGHT		212°F Miscible 91.0	pH (CONC.) pH (USE DIL EVAPORATION	UTION) RTU RATE (Water=1)	9.2 ± 0.2 9.2 ± 0.2 1.0
SECTIC BOILING F SOLUBILI % VOLATI SPECIFIC (ON III - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY	SICAL DAT	7A 212°F Miscible 91.0 0.98	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F	UTION) RTU RATE (Water=1) ORM	9.2 ± 0.2 9.2 ± 0.2
SECTIC BOILING F SOLUBILIT W VOLATI SPECIFIC O APPEARAL	ON III - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR	Off-V	TA 212°F Miscible 91.0 0.98 White Emulsion; Lemo	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F	UTION) RTU RATE (Water=1) ORM	9.2 ± 0.2 9.2 ± 0.2 1.0
SECTION BOILING FOR SOLUBILITY WOLATION SPECIFIC CAPPEARANTS SECTION S	ON III - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR	Off-VE AND EXP	212°F Miscible 91.0 0.98 White Emulsion; Lemo	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F	RATE (Water=1) ORM	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTIC BOILING F SOLUBILIT VOLATI SPECIFIC APPEARAN SECTIC FLASH PO	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR UNT (Test Method)	Off-V E AND EXP	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragra	UTION) RTU RATE (Water=1) ORM nce FLAMMABI	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTIC BOILING F SOLUBILIT WOLATI SPECIFIC C APPEARA SECTIC FLASH PO EXTINGUIS	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR WINT (Test Method) SHING MEDIA	Off-V E AND EXP CO ₂ , Foam, Dry	212°F Miscible 91.0 0.98 White Emulsion; Lemo	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran	UTION) RTU RATE (Water=1) ORM nce FLAMMABI	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTIC BOILING F SOLUBILIT WOLATI SPECIFIC C APPEARA SECTIC FLASH PO EXTINGUIS	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR UNT (Test Method)	Off-V E AND EXP CO ₂ , Foam, Dry	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragra	UTION) RTU RATE (Water=1) ORM nce FLAMMABI	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOOLUBILITY WOLATI SPECIFIC CAPPEARAI SECTION FLASH POEXTINGUIS SPECIAL FILE	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR WINT (Test Method) SHING MEDIA	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOOLUBILITY WOLATI SPECIFIC CAPPEARAI SECTION FLASH POEXTINGUIS SPECIAL FILE	PON III - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR HINT (Test Method) SHING MEDIA RE FIGHTING PROC	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None.	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOOLUBILITY WOLATI SPECIFIC OF APPEARAN SECTION FLASH POPECIAL FILL BETTE SPECIAL FILL BETTE SPECIAL FILL BUNUSUAL FOOLUBER SPECIAL FILL BUNUSUAL FILL BUNUSUA FILL BUNUSUA FILL BUNUSUA FILL BUNUSUA F	PON III - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR HINT (Test Method) SHING MEDIA RE FIGHTING PROC	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES	212°F Miscible 91.0 0.98 White Emulsion; Lemo CLOSION DATA Closed Cup: None Chemical, Water	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None. Products of	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
BOILING FOOLUBILITY SOLUBILITY VOLATI VOLATI SPECIFIC OF SPECIAL FOOLUBILITY SECTION SECTION SPECIAL FILE SECTION SPECIAL FILE SECTION SECTION SECTION SPECIAL FILE SECTION SE	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR MINT (Test Method) SHING MEDIA RE FIGHTING PROC	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None Chemical, Water	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None. Products of	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOOLUBILITY WOLATI FOR SPECIFIC OF APPEARAN SECTION FLASH POPECIAL FURNISHED FOR SECTION SECTI	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR MINT (Test Method) SHING MEDIA RE FIGHTING PROC	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES ON HAZARDS CTIVITY D Stable	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None Chemical, Water	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None. Products of	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOOLUBILITY WE VOLATE SPECIFIC OF APPEARANT SECTION FLASH POPEARANT SECTION FLASH POPEARANT SECTION SE	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR DINT (Test Method) SHING MEDIA RE FIGHTING PROC FIRE AND EXPLOSI ON V - REA Y ONS TO AVOID	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES ON HAZARDS CTIVITY D Stable None	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None Chemical, Water	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None. Products of co	UTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid
SECTION BOILING FOR SOLUBILITY WOLATI SPECIFIC CAPPEARAN SECTION FLASH POPEXTINGUIS SPECIAL FILL SECTION STABILITY CONDITION INCOMPA	POINT - PHY POINT °F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR DINT (Test Method) SHING MEDIA RE FIGHTING PROC FIRE AND EXPLOSI ON V - REA Y ONS TO AVOID	Off-V E AND EXP Tag CO ₂ , Foam, Dry CEDURES ON HAZARDS CTIVITY D Stable None Acids	212°F Miscible 91.0 0.98 White Emulsion; Lemo LOSION DATA Closed Cup: None Chemical, Water	pH (CONC.) pH (USE DIL EVAPORATION PRODUCT F on-Lime Fragran UPPER LIMI None. Products of co	AUTION) RTU RATE (Water=1) ORM nce FLAMMABI T: NA combustion.	9.2 ± 0.2 9.2 ± 0.2 1.0 Liquid

BUCKEYE EQUITY CODE: 5108

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? No SKIN? Yes INGESTION? No

HEALTH HAZARDS (Acute and Chronic)

Slight eye irritant. Moderate skin irritant.

Not toxic by ingestion.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

SIGNS AND SYMPTOMS OF OVEREXPOSURE

For Eyes: Redness or burning sensation.

For Skin: Redness of skin or a warming sensation.

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY EXPOSURE

May aggravate existing dermatitis.

EMERGENCY AND FIRST AID PROCEDURES

For Eyes: Flush with cool water for 15 minutes. If

irritation occurs and persists, see physician. For Skin: Flush with water for 15 minutes. If irritation occurs and persists, see physician. For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Call physician. Never give anything by mouth to an unconscious person.

SECTION VII - SPILL OR LEAK PROCEDURES

SPILL RESPONSE

Pick up with mop or wet/dry vac or with inert absorbent. Clean area with detergent and water. Rinse

area with clear water and allow to dry before allowing traffic to resume.

WASTE DISPOSAL

METHOD Dispose of in sanitary landfill according to federal, state and local laws.

SECTION VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION When eye contact may occur, VENTILATION

wear safety glasses or chemical splash goggles. Normal room ventilation.

SKIN Rubber gloves or other RESPIRATORY

PROTECTION impervious gloves. PROTECTION None required.

OTHER

PROTECTION Wash thoroughly with soap and water after handling.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS IN KEEP OUT OF REACH OF CHILDREN!

HANDLING AND STORAGE Keep from freezing!

Keep container closed when not in use.

Store at room temperature.

OTHER This product is not regulated under CERCLA or RCRA.

PRECAUTIONS Not reportable under SARA Title III, Section 311/312.

NA = Not Applicable NE = Not Established

PREPARED BY: Scott Maag, Director of Research

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.