KRYLON DIV OF SHERWIN WILLIAMS -- 21-201 ALUMINUM NOW SPRAY PAINT -- 8010-00F047094

======= Product Identification ============

Product ID:21-201 ALUMINUM NOW SPRAY PAINT MSDS Date:05/01/1992 FSC:8010 NIIN:00F047094 MSDS Number: BZCGX === Responsible Party === Company Name: KRYLON DIV OF SHERWIN WILLIAMS Address:31500 SOLON RD City:SOLON State:OH ZIP:44139-3908 Country: US Info Phone Num: 216-292-7400/800-832-2541 Emergency Phone Num:216-292-7400/800-832-2541 CAGE: KRYLO === Contractor Identification === Company Name: KRYLON DIV OF SHERWIN WILLIAMS Address:6830 COCHRAN RD City:SOLON State: OH ZIP:44139-3908 Country: US Phone: 216-292-7400/800-832-2541 CAGE: KRYLO ====== Composition/Information on Ingredients ======== Ingred Name:PROPANE (DIMETHYLMETHANE) *96-1* CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 15% Other REC Limits: 1800 MG/CUM OSHA PEL:1000 PPM ACGIH TLV:SIMPLE ASPHYXIANT Ingred Name: ISOBUTANE, 2-METHYLPROPANE CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 15% Other REC Limits: 1000 PPM OSHA PEL:1800 MG/CUM ACGIH TLV:1000 PPM Ingred Name:TOLUENE (IARC CARC- GROUP 3) *96-1* CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 53% Other REC Limits: 375 MG/CUM OSHA PEL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name: TRIMETHYL BENZENE

CAS:25551-13-7
RTECS #:DC3220000
Fraction by Wt: 3%

Other REC Limits:25 PPM

OSHA PEL:25 PPM

ACGIH TLV:123 MG/CUM

Ingred Name:ETHYLTOLUENE

96-1

CAS:25550-14-5 Fraction by Wt: 1%

Ingred Name: SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH

AROMATIC NAPHTHA *96-1*

CAS:64742-95-6 RTECS #:WF3400000 Fraction by Wt: 4%

Ingred Name:VOLATILE ORGANIC CONTENT: 95%/WT

Explanation of Carcinogenicity:NONE

RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE IRRITATION OF EYES, SKIN &
RESPIRATORY SYSTEM & NERVOUS SYSTEM DEPRESSION. EXTREME
OVEREXPOSURE MAY RESULT IN POSSIBLY DEATH. PROLONGED OVEREXPOSURE
TO SOLVENTS MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY,
BLOOD-FORMING CARDIOVASCULAR & REPROCUTIVE SYSTEMS. (SEE SUPP)

Effects of Overexposure: IRRITATION, UNCONSCIOUSNESS, HEADACHE, DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDNESS, ITCHING, BURNING SENSATION

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AREA THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CAS ES.

======== Fire Fighting Measures ==============

Flash Point Method: PMCC

Flash Point:<0F Lower Limits:1 Upper Limits:12.8

Extinguishing Media: CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures: WEAR FULL PROTECTIVE EQUIPMENT W/SCBA. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO THE BUILDUP OF PRESSURE WHEN EXPOSED TO EXTREME HEAT. VAPORS WILL ACCUMULATE READILY & MAY IGNITE EXPLOSIVELY.

======================================
Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE & REMOVE W/INERT ABSORBENT.
======================================
Handling and Storage Precautions: KEEP FROM IGNITION SOURCES. DON'T PUNCTURE/INCINERATE/EXPOSE TO TEMP >120F. USE APPROVED BONDING & GROUNDING PROCEDURES. KEEP OUT OF REACH OF CHILDREN Other Precautions: DURING USE & UNTIL ALL VAPORS ARE GONE, KEEP AREA VENTILATED, DON'T SMOKE, EXTINGUISH FLAME/IGNITION SOURCE. DON'T TAKE INTERNALLY. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF EXPOSURE CAN'T BE CONTROLLED 1 Evaporation Rate & Reference:FASTER THAN ETHER
========== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, ELECTRICAL EQUIPMENT, TEMPS >120F, SUNLIGHT/OTHER IGNITION SOURCES. Hazardous Decomposition Products:BY FIRE: CO2, CO
========== Disposal Considerations ==============

Waste Disposal Methods: WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DON'T INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.