PENNZOIL® ROADSIDETM FIX-A-FLAT®

PRODUCT AND COMPANY IDENTIFICATION MSDS Number: 13380 Version Date: 10/15/00

Product Name: PENNZOIL® ROADSIDE™ FIX-A-FLAT®

Product Use: Seal & inflate automotive tires

Synonyms: PENNZOIL® ROADSIDE™ SUPER FIX-A-FLAT®, S410, S420, S430

Phone Numbers Manufacturer

Pennzoil-Quaker State Company **Medical Emergency:** 1-800-546-6040 CHEMTREC(USA): 1-800-424-9300 P.O. Box 2967

CHEMTREC(International): 1-703-527-3887 Houston, TX 772522967 USA

MSDS Assistance: 1-800-546-6227 Fax On Demand: 1-800-546-6227 Technical Assistance: 1-800-416-1600 Customer Service: 1-800-468-8397

Fax Number: 713-217-3181

Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
WATER	7732-18-5	30 - 60	No
TETRAFLUOROETHANE	811-97-2	10 - 55	Yes
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	10 - 50	Yes
AMORPHOUS POLYOLEFIN	MIXTURE	< 15	No
AROMATIC RESIN	MIXTURE	< 10	No
INERT FILLER	MIXTURE	< 7	No
EMULSIFIER	TRADESECRET	1 - 8	No

This product is HAZARDOUS according to the Hazards: Flammable/Combustible Pressure X Reactive	Acute Toxin X	Chronic Toxin	_
Other: No information available			
3. HAZARDS IDENTIFICATIO	ON		
Emergency and Hazards Overvion DANGER: HARMFUL OR FATA CAUSE EYE IRRITATION.		D. CONTENTS UND	ER PRESSURE. MAY
NFPA Ratings: Health 1	Flammability _	1 Reactivity 0	_
Primary Route of Exposure: S	Skin <u>X</u> Inhalati	on Eye	
Health Effect Information Eve Contact: Avoid eve contact	t Exposure to mists	and vanors may be irrit	ating to the eyes. May be

ct: Avoid eye contact. Exposure to mists and vapors may be irritating to the eyes. May be irritating to the eyes upon direct contact.

Skin Contact: Avoid skin contact. This product may cause skin irritation upon direct contact. Prolonged or repeated skin contact may result in dryness, chapping, and reddening. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route. May be absorbed through skin.

Inhalation: This product is not expected to pose an inhalation hazard under conditions of forseeable use. Avoid prolonged inhalation of vapors. Acute and chronic overexposures may be irritating to the respiratory tract. Inhalation of high concentrations of this product can cause central nervous system depression and narcosis. Severe intoxication may lead to drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Exposure to extremely high concentrations may have anesthetic effects but are completely reversible upon cessation of exposure. Inhalation of high vapor concentrations may cause heart irregularities, including irregular pulse, palpitation and inadequate circulation. Vapors are heavier than air and can settle in low lying areas such as pits. Intentional misuse by deliberately concentrating and/or inhaling can be harmful or fatal.

Ingestion: Ingestion is unlikely for aerosol products. This product is regarded as having a low order of toxicity.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease. Individuals with preexisting diseases of the central nervous system or cardiovascular system may have increased susceptibility to this product.

Other: No information available

MSDS Number: 13380

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: Wash contaminated area thoroughly with soap and water. If redness or irritation persists, seek medical attention.

Inhalation: If victim exhibits signs of vapor intoxication remove to fresh air. If discomfort persists seek medical attention.

Ingestion: Ingestion is unlikely for aerosol products. Accidental spraying into the mouth will not result in any harmful effects. Do not induce vomiting due to aspiration hazard.

Notes to Physician: Because of possible disturbances of cardiac rhythm, catecholamine drugs such as epinephrine, should be used with caution, and only in emergency situations.

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point (aerosol concentrate): None

Flame Extension: 0", no flashback

Test Method: Setaflash

Test Method: CPSC 1500.45

Flammable Limits in Air

Upper Percent: No data available **Lower Percent:** No data available

Autoignition Temperature: No data available **Test Method:** No information available

NFPA Classification: No information available

Extinguishing Media: Use water spray (fog), dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: This material is nonflammable.

PENNZOIL® ROADSIDETM FIX-A-FLAT®

Unusual Fire and Explosion Conditions: Caution! Contents are under pressure and can explode when exposed to heat or flames. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 C. Do not pierce or burn even after container is empty.

Hazardous Combustion By-Products: Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Other: No information available

MSDS Number: 13380

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Provide adequate ventilation during clean-up.

Regulatory Notifications: No notification required

Containment and Clean up: No special cleanup procedures are necessary.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: Contents under pressure and can explode when exposed to heat or open flame. Caution!--Do not puncture or incinerate. Do not weld on a rim without first removing the tire from the rim. Failure to do so could cause the tire to explode regardless of whether tire inflator is used. Welded and repaired rims are unsafe.

Storage: Do not store at temperatures greater than 120 F.

Empty Container Warnings
Drums: Not applicable
Plastic: Not applicable

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

Component	CAS No.	Exposure Limit
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	OSHA - PEL: TWA 500 ppm
		ACGIH - TLV: TWA 100 ppm

Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with unperforated sideshields.

Skin Protection: Skin protection is not required under conditions of normal use. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes.

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If excessive levels of mists or vapors are generated while using this product, use an organic vapor respirator. All respirators must be NIOSH certified.

Personal Hygiene: Always wash hands and face with soap and water before eating, drinking, or smoking. Consumption of food and beverage should be avoided in work areas where this product is present.

Page 3 of 8

Engineering Controls / Work Practices

Ventilation: All use, including deflating of tires, must be done in a well-ventilated area. If product is used in enclosed or confined spaces, adequate ventilation must be provided to prevent buildup of vapors or mists.

Other: No information available

MSDS Number: 13380

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Foamy, milky liquid	
Odor: Ammonia - mild	Vapor Pressure: 77 - 79 psig @ 68 F
Physical state: Liquid	Vapor Density (air=1): < 1
pH: 8.5 - 9.5	Percent Volatile by Volume: Apx 92 %
Boiling Point: 30 F, -1.1 C	Volatile Organic Content: No data available
Melting Point: No data available	Molecular Weight: No data available
Specific Gravity: Apx 0.98	Average Carbon Number: No data available
Pour Point: -15 F, -26.1 C	Viscosity @ 100 F: 20 SUS
	Viscosity @ 40 C: No data available
Solubility in Water: Soluble in water	
Octanol / Water Coefficient: Log K _{ow} = No data a	vailable

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: High heat and open flames.

Incompatible Materials to Avoid: Avoid contact with magnesium.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: The IARC has concluded that petroleum solvents are Group 3 substances, "not classifiable as to their carcinogenicity to humans". This product is not considered to be carcinogenic.

PENNZOIL® ROADSIDETM FIX-A-FLAT®

Page 4 of 8

MSDS Number: 13380 PENNZOIL® ROADSIDE™ FIX-A-FLAT® Page 5 of 8

Reproductive and I	Developmental	Toxicity: No	o information available
•	-	•	

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly.

Waste Disposal Methods: No special waste disposal methods are required. Waste material may be

landfilled or incinerated at an approved facility.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated

Highway / Rail (Non-Bulk): CONSUMER COMMODITY - ORM-D

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

International Information

Other: No information available

15. Regulatory Information

<u>Regulatory Lists Searched</u> The components listed in Section 2 of this MSDS were compared to substances which appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 21 - USDOT Appendix B, Marine pollutants, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

PENNZOIL® ROADSIDETM FIX-A-FLAT®

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA

Regulatory Search Results:

HEAVY AROMATIC SOLVENT NAPHTHA: 80, 81, 83, 84

TETRAFLUOROETHANE: 65, 80, 81, 82, 83, 84

WATER: 80, 81, 83, 84

MSDS Number: 13380

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.

IARC: No information available	
SARA 311 / 312 Categories Acute: X Chronic: Fire: Not Regulated:	Pressure: X Reactive:
Canadian WHMIS Classification	

Class A Compressed gas

Poisonous and infectious material, Division 2, Subdivision B Toxic material Class D

European Union Classification

Hazard Symbols:

"3" / Aerosol

Harmful / Xn / X in square.

Risk Phrases:

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety Phrases:

S2: Keep out of the reach of Children.

S23: Do not breathe gas/fumes/vapour/spray.

S24: Avoid contact with skin.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Other: No information available

16. OTHER INFORMATION

Page 6 of 8

PENNZOIL® ROADSIDETM FIX-A-FLAT® Page 7 of 8

Health and Environmental Label Language

Front Label:

MSDS Number: 13380

DANGER: HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

MAY CAUSE EYE IRRITATION.

Read all cautions and directions on back panel before using.

Back Label:

DANGER: PRECAUTIONARY MEASURES:

DO NOT ingest or inhale. Use in a well ventilated area. Avoid contact with eyes.

DO NOT puncture or incinerate container. DO NOT expose to heat, open flame, direct sunlight or store at temperatures above 120° F. Exposure to heat may cause can to rupture. DO NOT STORE

IN INTERIOR OF CAR (INCLUDING GLOVE COMPARTMENT AND INSIDE

HATCHBACKS). TEMPERATURES INSIDE CAR CAN EXCEED 120° F. STORE OUTSIDE PASSENGER AREA OF VEHICLE PREFERABLY SECURED IN SPARE TIRE WELL OR TRUNK.

DO NOT use with any other tire inflator products.

DO NOT use on motorcycle tires. Failure of one tire could cause loss of control. Also DO NOT use on high performance or "Z-rated" tires.

DO NOT use Fix-A-Flat with tires which utilize tire sensor technology. Fix-A-Flat may block tire sensors and cause them to be inoperable. Fix-A-Flat will not be liable for damage to tire sensors. NEVER WELD ON A RIM. WELDING ON A RIM WITH THE TIRE MOUNTED COULD CAUSE THE TIRE TO EXPLODE REGARDLESS OF WHETHER TIRE INFLATOR IS USED. WELDED AND REPAIRED RIMS ARE UNSAFE.

FIRST AID: Contains fluorocarbons and aromatic solvents.

INHALATION: If inhaled, breathe fresh air. If breathing is affected, give artificial respiration and call a physician.

EYE CONTACT: Immediately flush with water for 15 minutes. If irritation persists, call physician.

INGESTION: If ingested, do not induce vomiting. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN.

For health emergency call: 1-800-546-6040.

MSDS Revisions

Previous Version Date: 03/02/99

Previous Version Information: Product formulation changed.

Other: No information available

Prepared By:

Pennzoil-Quaker State Company Environmental, Safety, Health, & DOT Compliance P.O. Box 2967 Houston, TX 77252-2967 USA

MSDS Number: 13380

PENNZOIL® ROADSIDETM FIX-A-FLAT®

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgement. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Pennzoil-Quaker State Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 8 of 8