MATERIAL SAFETY DATA SHEET

For compliance with OHSA's 29 CFR 19101200 and Bill No. 70 WHMIS Hazard Communications Standards

Section 1: Company and Product Identification

Product Name: Chemical Name:

Cone 04-06 Clays: Hydrous Alumina Silicate

Casting Slip

Company Name and Address:

Aardvark Clay & Supplies, Inc.

Telephone Number: (714)541-4157

1400 E. Pomona Street

Santa Ana, Ca 92705 Facsimile Number: (714)541-2021

Section 2: Potential Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name) may contain:

OSHA/PEL ACGIH/TLV CAL-OSHA/PEL

Crystalline Silica (Quartz) 0.1mg/M3 0.1mg/M3 0.1mg/M3

Silica CAS #14808-60-7

Talc CAS #14807-96-6 2 mg/cu m 2 mg/cu m 2 mg/cu m

Section 3: Physical Data

Solubility in Water Negligible

Appearance Color Variable, Off-white

Odor Earthy
Specific Gravity ($H^2O = 1$)
Melting Point Above 2
Above 2000 F

Boiling Point N/A % Volatile by Volume N/A

Section 4: Fire and Explosion Data

Non-flammable

Section 5: Health Hazard Data

Exposure Limits

Respirable Crystalline Quartz OSHA PEL = 0.10 mg/m3ACGIH TLV = 0.10 mg/m3

ACOIII ILV = 0.10iiig/iii3

Route of Entry: Inhalation, Eyes, Skin, Ingestion. Aardvark clays in moist form do not present an inhalation health hazard as evaluated under ASTM4236.

<u>In dry form</u> this product contains a chemical (crystalline silica) known to the State of California to cause cancer. (Prop. 65 – Calif. Health & Safety Code Section 25249 Et Seq.) Excessive inhalation of dust may result in respiratory disease including silicosis, pneumoconiosis, and pulmonary fibrosis. The International Agency for Research on Cancer (IARC) has evaluated in Volume 42, Monograghs on the Evaluation of the Carcinogenicity Risk of Chemicals Risk of Chemical to Humans, Silica and Some Silicates (1987), that there is sufficient evidence for the carcinogenicity of crystalline silica to experimental animals and limited evidence with respect to humans.

First Aid

Inhalation (Respiratory or breathing problem): Skin: Eyes:

Remove from dust and consult physician Flush with water Flush with Water

SECTION 6: REACTIVITY DATA

Stability Stable Incompatibility None Hazardous Decomposition None

Hazardous Polymerization Will not occur

Section 7: Spill, Leak, and Disposal Procedures

If uncontaminated, sweep or vacuum and reuse as product.

If contaminated, collect in suitable container. Avoid generating dust.

Dispose of in an approved landfill facility in accordance with the applicable federal, state, and local regulations.

Section 8: Special Protection Information

Respiratory Protection:

Use NIOSH/MSHA approved respirator if exposure exceeds TLV.

Ventilation:

Use local exhaust.

Eye Protection:

Use NIOSH/OSHA approved safety glasses

Skin Protection:

Latex gloves may be used for those persons with sensitive skin.

Section 9: Transportation Requirements

This product is not considered hazardous by D.O.T. regulations.

Section 10: Regulatory Information

This product may contain components that require reporting under Section 313 of the Emergency Planning and Community Right to Know Act (Superfund Amendments and Reauthorization Act), and 40CFR Part 372

SARA TITTLE III DATA:

Reportable Items under OSHA regulations [29 CFR 1910.1200(C)]: Quartz

Section 11: Additional Information

Wear NIOSH/MSHA approved dust mask when working in dust conditions.

Food, beverages and smoking materials should NOT be in the work area. Persons using ceramic materials should wash thoroughly before eating, drinking, smoking or applying cosmetics.

THIS MATERIAL SAFETY DATA SHEET IS FURNISHED WITHOUT CHARGE TO RESPONSIBLE PERSONS WHO USE IT AT THEIR DISCRETION AND RISK. ALTHOUGH THE INFORMATION AND SUGGESTIONS CONTAINED HEREIN HAVE BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, THERE IS NO WARRANTY OF ANY KIND EXPRESSED OR IMPLIED. AS TO THE COMPLETENESS OR ACCURACY THEREOF.

MSDS Preparation Date: November 15, 1999 This data sheet is subject to change without notice.